Computational Fluid Dynamics (AE/ME 339) MAE Dept.

Home Work Problem

This problem involves free convection flow at a heated vertical wall and the numerical solution of the simplified non-dimensionalized equations. Use the explicit method as discussed in class.

Solve for the dependent variables U_bar , V_bar , and θ . Use the initial and boundary conditions are follows:

$$\begin{split} \tau &= 0 \colon \\ U_bar &= V_bar = 0, \, \theta = 0. \end{split}$$

$$\begin{aligned} \tau &> 0 \colon \\ \xi &= 0 \colon & U_bar = V_bar = 0, \, \theta = 0. \text{ (bottom wall)} \\ \eta &= 0 \colon & U_bar = V_bar = 0, \, \theta = 1. \text{ (vertical wall)} \\ \eta &= &\inf \text{infinity:} & U_bar = 0, \, \theta = 0. \end{split}$$

Use the following for dimensional calculations: $T_{\rm W}$ = 50 C, and $T_{\rm infty}$ = 20 C. Assume that the coefficient of thermal expansion is constant and is given by the following expression.


$$\beta = \frac{1}{\left(\frac{T_w + T_\infty}{2} + 273\right)} \dots (1/K)$$

The time step must satisfy the approximate stability criterion given below.

$$\frac{\Delta \tau}{\left(\Delta \eta\right)^2} \le \frac{1}{2}$$

For the finite domain for your calculation choose ξ _max = 100, and η -max = 25. Use $\Delta \xi = 10$, $\Delta \eta = 2.5$ and $\Delta \tau = 0.5$.

- 1. Prepare a detailed flow diagram of the calculations that you will be doing.
- 2. Calculate the variables at $\tau = 80$. Show the result in tabular form as indicated in the figure given below. Plot the distributions of the <u>dimensional</u> velocities and temperature along a horizontal line where ($\xi = \xi_{max}/2.0$).
- 3. Write a short note describing the procedure, details of the calculations and discussion of the results. Attach a listing of your computer program.



Make 3 tables for U, V, and theta values for the nodes Choose print interval such that you show only 10 values in each directions at equally spaced nodes.