

turtle wax, inc 5655 West 73rd St. Chicago, Illinois 60638-6211

Material Safety Data Sheet

EMERGENCY SPILL PHONE: 1 (800) 424-9300 (CHEMTREC)

MSDS No: T-244(C)

EMERGENCY MEDICAL PHONE: (Contact your local poison control center)

PRODUCT INFORMATION PHONE: 1 (708) 563-3600

NFPA Hazard Ratings: Health 1, Flammability 2, Reactivity 0

HMIS Hazard Ratings: Health 1, Flammability 2, Reactivity 0, Protection B

Prepared By: Research and Development, Phone: 1 (708) 563-3600

Date Issued: August 6, 2003

1 - MATERIAL IDENTIFICATION

PRODUCT NAME: TURTLE WAX POWER OUT CARPET CLEANER AND PROTECTOR, T-244(C)

Chemical Family: Mixture: water, solvent, surfactants, additives.

Material Use or Occurrence: Carpet cleaner. Product Identification No.: UN 1950 (Canada)

2 - IMPORTANT INGREDIENTS

CHEMICAL NAME	CAS No.	PERCENT	PEL/TLV/TWA		CARCINOGEN
(Synonyms)		7-10%	OSHA 100ppm100p		(OSHA,NPT,IARC)
Propylene Glycol Methyl Ether (Glycol Ether PM)			,		No
Isobutane (Liquified Petroleum Gas)	75-28- 5	3-5%	1000ppm	1000ppm	140

3 - CHEMICAL AND PHYSICAL PROPERTIES

Boiling Point: n/av Specific Gravity: 1.010 Solubility in Water: Complete

Evaporation Rate: n/av

Coefficient of Oil/Water Distribution: n/av

Melting Point: n/av

Vapor Pressure: 35 PSIG @ 70°F Vapor Density (Air=1): n/av % Non-volatile: 8.0%

pH: 9.8

Appearance and Odor: Hazy White translucent liquid with white foam. Odor: typical.

4 - FIRE AND EXPLOSION DATA

Flash Point (Seta Flash Cl. Cup): Sprayed vapors can be ignited with a flame. Flame length 14-16 inches, with no flash back to nozzle by CPSC test 16CFR 1500.3(b)(6)(viii); rated not flammable.

Explosive Limits: Lower: n/av

Upper: n/av

NFPA-30 Aerosol Level I

Extinguishing Media: Water spray, Carbon Dioxide, Chemical Foam, Dry Chemical.

Special Fire Fighting Procedures and Hazards: Aerosol cans are under pressure, can explode when heated above about 140°F, and can become projectiles. Treat contents as flammable liquid/explosive vapor fire. unignited containers cool with water. Vapors that are heavier than air, may collect in low areas, and may travel to distant source of ignition and flashback. Avoid flow of material into sewers. See Sec. 6 for personal protection.

5 - REACTIVITY INFORMATION

Stable: X

Unstable:

Precautions: None Does Not Occur: X

Hazardous Polymerization Occurs:

Incompatibility: Strong oxidizers such as peroxides.

Hazardous Decomposition Product: When burned: CO₂, CO, Hydrocarbons.

Turde Wax, Inc. MSDS No. T-244R(C) - August 6, 2003

6 - HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

- Repeated or excessive inhalation of vapor, mist or spray can cause irritation, chemical pneumonia, dizziness, and nausea. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. chronic effects known.
- Use NIOSH approved respirator appropriate for concentration of vapor or mist. Provide good ventilation.
- Remove to fresh air. Use artificial respiration and oxygen if needed.

Skin:

- Repeated or excessive contact can cause blisters or rash due to defatting action. No chronic effects known.
- Wear solvent resistant gloves and other clothing as needed to prevent exposure.
- Remove contaminated dothing, and avoid ignition sources. Wash effected areas thoroughly with soap and

Eves:

- Causes irritation. No chronic effects known.
- Wear goggles. Have convenient eye wash stations.
- Flush with water for 15 minutes. Get medical attention if effects persist.

- Causes digestive system upsets, dizziness, nausea, and may be fatal. If sucked into lungs, effects are same as for inhalation above. No chronic effects known.
- Avoid swallowing or sucking into lungs. Wear face shield if face contact is likely.
- Rinse mouth. Do not induce vomiting. Get prompt medical attention especially if liquid is sucked into lungs

IN ALL CASES: GET PROMPT MEDICAL ATTENTION IF EFFECTS PERSIST.

KEEP OUT OF REACH OF CHILDREN.

Most likely routes of entry: Skin, Eyes

7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills and Leaks: Remove all ignition sources, and use spark proof equipment. Provide good ventilation. Take up spills with absorbent or by pumping and put into closed containers. Avoid flow to sewers. Floors may be slippery. See Section 6 for other protective measures.

Storage and Handling: Keep away from ignition or heat source. Store in cool and ventilated places, but avoid freezing. Keep containers closed.

Waste Disposal: In accordance with applicable local, state, and federal regulations.

Empty Containers: Do not cut or weld on empty containers before thoroughly cleaning. Rinse thoroughly before handling, reuse, or disposal.

8 - REGULATORY INFORMATION

DOT(HM-181) USA & Int'l:

For inner containers of less than 1 liter (33.8 ounces) each, less than 66 lb. total package weight, and not shipped by air.

Class and Label: ORM-D

Shipping description: None Required (May use "Consumer Commodity")

For inner containers of more than 1 liter each (33.8 ounces), over 66 lb. total package weight, or shipped by air:

Class and Label: 2.2 Non-flammable gas.

Shipping description: Aerosols, non-flammable (each not exceeding 1 L capacity), 2.2, UN1950.

SARA.Title III: Reportable for Section 313(Form R):

TSCA INVENTORY: All ingredients are commercially available and presumed to be listed by manufacturer.

CALIFORNIA PROP. 65: No listed substances are known to be present.

NEW JERSEY LABEL INGREDIENTS: Water (CAS# 7732-18-5), Sodium Lauryl Sulfate (CAS # 151-21-3), Propylene Glycol Methyl Ether (CAS # 107-98-2), Sodium Lauroyl Sarcosinate (CAS # 97-78-9), Isobutane (CAS # 7**5-28-5**).

CANADA EPA DSL INVENTORY: Consult Turtle Wax, Inc. regarding status of ingredients.

EEC SIXTH AMENDMENT INVENTORY: Consult Turtle Wax, Inc. regarding status of ingredients.

The information contained here in has been compiled from sources believed to be reliable and is accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Recipient assumes all responsibility for the use of this information and the use, storage, or disposal of the product, including any resultant personal injury or property damage.